



## RF KEY - Remote Key Fob (4 Channel)



- RF KEY-W: 4-channel (fold) key fob in white
- RF KEY-B: 4-channel (fold) key fob in black
- The Key-fob is a portable transmitter for controlling the various receivers available
- Thanks to its small size it has a variety of uses; controlling entrance gates and garage doors as well as switching and dimming of lights
- Key-fob transmitters can simultaneously operate unlimited numbers of assigned receivers, which are within the range of transmitting signal
- The signal is transmitted by wireless communication between system units
- The range of the signal is dependent on building construction, applied materials and concept of unit location
- Both these transmitters are powered by battery (CR 2032)
- The battery life is approximately 3 to 5 years (depending on frequency of use)

Technical Details	
Supply voltage:	3V battery CR 2032
Transmission indication:	Red LED
Number of inputs:	4
Transmission frequency:	868 MHz
Type of signal transmision:	Unidirectionally addressed message
Range in open space:	Up to 200 M
Other data	
Operating temperature:	-10 °C to +50 °C (14 °F to 122°F)
Operating position:	Any
Protection degree:	IP20
Pollution degree:	2
Dimensions:	64 x 25 x 10 mm
Weight:	16 g
Applicable standards:	EN 60669, EN 300 220, EN 301 489
	Directive RTTE, No.426/2000Sb (Directive 1999/ES)
Warranty:	12 Months

Transmission indication

Control buttons





Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362

 $\textbf{E}: sales@scolmore.com \mid \textbf{W:} scolmore.com$ 

